

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List)

Spray Adhesive CMD-11A

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

| | |
|--|--|
| Manufacturer's Name Crow Marketing & Distribution, Inc. | Emergency Telephone Number 800-255-3924 |
| Address (Number, Street, City, State, and ZIP Code) P. O. Box 29171, Dallas, TX 75229 | Telephone Number for Information 972-241-3049 |
| | Date Prepared 09-09-91 REVIEWED 12/01/99 |
| | Signature of Preparer (Optional) |

Section II -- Hazardous Ingredients/Identity Information

| Hazardous Components (Specific Chemical Identity; Common Name(s)) | OSHA PEL | ACGIH TLV | Other Limits Recommended | % (optional) |
|---|----------|-----------|--------------------------|--------------|
| Dichloromethane | 500 pm | 50 ppm | CAS# 75-09-2 | |
| n-Hexane (1) | 500 ppm | 50 ppm | 110-54-3 | |
| Propane | 1000 ppm | 1000 ppm | 74-98-6 | |
| Isobutane | Not Est. | 800 ppm | 75-28-5 | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

Section III -- Physical/Chemical Characteristics

| | | | |
|---------------------------------|---------|---|------|
| Boiling Point | N/A | Specific Gravity (H ₂ O = 1) at 25°C | .768 |
| Vapor Pressure (mm Hg.) at 25°C | 80 psig | Melting Point | N/A |
| Vapor Density (AIR = 1) | >1 | Evaporation Rate (Butyl Acetate = 1) | >1 |

Solubility in Water

Insoluble

Appearance and Odor

Light Amber - Sweet Etheral Odor

Section IV -- Fire and Explosion Hazard Data

| | | | |
|---|-----------------------------|----------------|----------------|
| Flash Point (Method Used) Flame Projection: 18" plus | Flammable Limits Unknown | LEL Unknown | UEL Unknown |
|---|-----------------------------|----------------|----------------|

Extinguishing Media

CO₂, Dry Chemical, Halon, Standard Foam

Special Fire Fighting Procedures

Wear self-contained breathing apparatus.

Unusual Fire and Explosion Hazards

Exposure to temperatures over 120°F may cause bursting or venting. Heat or flame may cause toxic fumes of Phosgene, Carbon Monoxide.

