

# Material Safety Data Sheet

May be used to comply with  
OSHA's Hazard Communication Standard,  
29 CFR 1910.1200. Standard must be  
consulted for specific requirements.

## U.S. Department of Labor

Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved  
OMB No. 1218-0072

**IDENTITY** (As Used on Label and List) *Coil Master Non Acid Coil Cleaner  
CMD-2A*

*Note: Blank spaces are not permitted. If any item is not applicable, or no  
information is available, the space must be marked to indicate that.*

### Section I

Manufacturer's Name Crow Marketing & Distribution, Inc.	Emergency Telephone Number 800-255-3924
Address (Number, Street, City, State, and ZIP Code) P. O. Box 29171, Dallas, TX 75229	Telephone Number for Information 972-245-4070
	Date Prepared 08-23-95 reviewed 08/19/06
	Signature of Preparer (Optional)

### Section II -- Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH	Other Limits Recommended	% (optional)
<i>NaOH Sodium Hydroxide 50%</i>	<i>2mg/m<sup>3</sup></i>	<i>2mg/m<sup>3</sup></i>		
<i>CAS#1310-73-2 NA1824 Corrosive</i>				

#### HMIS INFORMATION

<i>Health</i>	<i>2</i>
<i>Reactivity</i>	<i>1</i>
<i>Flammability</i>	<i>0</i>

### Section III -- Physical/Chemical Characteristics

Boiling Point <i>180°F</i>	Specific Gravity (H <sub>2</sub> O = 1) <i>1.01</i>
Vapor Pressure (mm Hg.) <i>760</i>	Melting Point <i>N/A</i>
Vapor Density (AIR = 1) <i>1</i>	Evaporation Rate (Butyl Acetate = 1) <i>N/A</i>

Solubility in Water

*Complete - 100%*

Appearance and Odor

*Yellow to gold liquid, characteristic odor*

### Section IV -- Fire and Explosion Hazard Data

Flash Point (Method Used) <i>None</i>	Flammable Limits <i>None</i>	LEL	UEL
--	---------------------------------	-----	-----

Extinguishing Media

*N/A*

Special Fire Fighting Procedures

*Will react with metals to produce flammable hydrogen gas*

Unusual Fire and Explosion Hazards

*None known. Contents under pressure. Exposure to temperatures above 120°F may cause bursting.*