

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As Used on Label and List)	Fin Saver CMD-33620	<i>Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.</i>
---	------------------------	--

Section I

Manufacturer's Name Crow Marketing & Distribution, Inc.	Emergency Telephone Number 800-255-3924
Address (Number, Street, City, State, and ZIP Code) P. O. Box 29171, Dallas, TX 75229	Telephone Number for Information 214-241-3049
	Date Prepared 03-30-92 REVIEWED 12/01/99
	Signature of Preparer (Optional)

Section II -- Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Solvent bases Acrylic Blend		Hazard Class	ORMD	
1) XYLENE FLAMMABLE LIQUID CAS #1330-20-7		100 PPM/8 hr.	100 PPM TWA	49
2) GLYCOL ETHER COMBUSTIBLE LIQUID CAS#111-76-2		25 PPM/SKIN		27
3) DYMEL 22 CAS#76-45-6				

1 & 2 are listed as toxic chemicals under SARA Title III Section 313
 2 is listed under CERCLA and as RCRA No. U239

		HMIS INFORMATION	
Spills of 2,000 lbs. or more must be reported.		Health	2
		Reactivity	0
Section III -- Physical/Chemical Characteristics		Flammability	3

Boiling Point 760° MM HG	280°F	Specific Gravity (H ₂ O = 1)	.93
Vapor Pressure (mm Hg.) Unknown	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	3.7	Evaporation Rate (Butyl Acetate = 1)	N/A

Solubility in Water
 Forms an emulsion
 Appearance and Odor
 Liquid blue in color, xylene odor

Section IV -- Fire and Explosion Hazard Data

Flash Point (Method Used) 80°F TAG CLOSED CUP	Flammable Limits N/A	LEL N/A	UEL N/A
--	-------------------------	------------	------------

Extinguishing Media
 Carbon Dioxide, Chemical Foam, Water Spray, Dry Chemical

Special Fire Fighting Procedures
 Use air-supplied breathing equipment for enclosed areas. Cool exposed containers with water spray. Avoid breathing fumes. Use eye protection.

Unusual Fire and Explosion Hazards

Do not mix or store with strong oxidizers. Material can accumulate static charges which can cause incendiary electrical discharge. Toxic gases upon burning.

Section V -- Reactivity Data

Stability	Unstable		Conditions to Avoid Open flames, sparks, strong oxidizers such as chlorine & peroxides
	Stable	X	

Incompatibility (*Materials to Avoid*)

Hazardous Decomposition or Byproducts

Carbon Monoxide

Hazardous Polymerization	May Occur		Conditions to Avoid N/A
	Will Not Occur	X	

Section VI -- Health Hazard Data

Route(s) of Entry:	Inhalation? Yes	Skin?	Ingestion? Yes
--------------------	--------------------	-------	-------------------

Health Hazards (*Acute and Chronic*)

INHALATION: Irritation in upper respiratory. INGESTION: Nausea, vomiting, diarrhea; SKIN: Irritation.

Carcinogenicity:	NTP? None	IARC Monographs? None	OSHA Regulated? None
------------------	--------------	--------------------------	-------------------------

Signs and Symptoms of Exposure

EYES: Redness and irritation; SKIN: redness & irritation; INGESTION: irritation of throat & mucous membrane; INHALATION: can cause dizziness, headache, nausea, unconsciousness.

Medical Conditions

Generally Aggravated by Exposure Not Determined

Emergency and First Aid Procedures

EYES: Flush with water 15 minutes, contact physician. SKIN: Wash well with soap & water; INHALATION: Remove victim to fresh air; INGESTION: Do not induce vomiting, call physician immediately, dilute by giving water if conscious.

Section VII -- Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

Remove ignition sources. Keep away from sanitary sewers and water sources. Contain and absorb.

Waste Disposal Method

Dispose of in accordance to all applicable federal, state and local environmental regulations.

Precautions to Be Taken in Handling and Storing

For industrial use only. Remove contaminated clothing, no smoking, keep containers tightly closed. Do not expose to open flames or ignition sources. Use in well ventilated areas.

Other Precautions

N/A

Section VIII -- Control Measures

Respiratory Protection (*Specify Type*)

Hydrocarbon vapor respirator or supplied air

Ventilation	Local Exhaust	Yes	Special
	Mechanical (<i>General</i>)		Other

Protective Gloves

Solvent resistant recommended

Eye Protection

Splash proof goggles or face shield

Other Protective Clothing or Equipment

N/A

Work/Hygienic Practices

Remove contaminated clothes, no smoking