

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List) *CMD-6A BUG MASTER*

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name <i>Crow Marketing & Dist., Inc.</i>	Emergency Telephone Number <i>(214) 241-3049</i>
Address (Number, Street, City, State, and ZIP Code) <i>P. O. Box 29171</i>	Telephone Number for Information <i>(241) 241-3049</i>
<i>Dallas, TX 75229</i>	Date Prepared <i>10-3-95 REVIEWED 10/11/2006</i>
	Signature of Preparer (Optional)

Section II -- Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
<i>1,1,1 Trichloroethane</i>	<i>350 ppm</i>	<i>350 ppm</i>	<i>71-55-6</i>	
<i>Kerosene</i>	<i>500 ppm</i>	<i>100 ppm</i>	<i>64742-65-7</i>	
<i>Resmethrin</i>	<i>Unknown</i>	<i>Unknown</i>	<i>104-53-86-8</i>	
<i>Carbon Dioxide</i>	<i>5000 ppm</i>	<i>5000 ppm</i>	<i>124-38-9</i>	

Section III -- Physical/Chemical Characteristics

Boiling Point	<i>N/A</i>	Specific Gravity (H ₂ O = 1)	<i>0.946</i>
Vapor Pressure (mm Hg.)	<i>80 psi</i>	Melting Point	<i>N/A</i>
Vapor Density (AIR = 1)	<i>1</i>	Evaporation Rate (Butyl Acetate = 1)	<i>1</i>
Solubility in Water <i>Insoluble</i>			
Appearance and Odor <i>Clear Straw Colored - Sweet Odor</i>			

Section IV -- Fire and Explosion Hazard Data

Flash Point (Method Used) <i>Flame Projection: 18"</i>	Flammable Limits <i>N/A</i>	LEL <i>N/A</i>	UEL <i>N/A</i>
Extinguishing Media <i>Standard Foam, CO₂, Dry Chemical, Halon</i>			
Special Fire Fighting Procedures <i>Wear self-contained breathing apparatus</i>			
Unusual Fire and Explosion Hazards <i>Exposure to temperature over 120°F may cause bursting or venting.</i>			
<i>Flames may cause decomposition of products: Carbon Monoxide, Phosgene.</i>			

Section V -- Reactivity Data

Stability	Unstable		Conditions to Avoid <i>N/A</i>
	Stable	X	<i>N/A</i>

Incompatibility (*Materials to Avoid*)

Oxidizing Materials

Hazardous Decomposition or Byproducts

Will not decompose

Hazardous Polymerization	May Occur		Conditions to Avoid <i>N/A</i>
	Will Not Occur	X	<i>N/A</i>

Section VI -- Health Hazard Data

Route(s) of Entry:	Inhalation? X	Skin? X	Ingestion? X
--------------------	------------------	------------	-----------------

Health Hazards (*Acute and Chronic*)

Acute effect may be produced from any route of entry.

Carcinogenicity:	NTP? <i>No</i>	IARC Monographs? <i>No</i>	OSHA Regulated? <i>No</i>
------------------	-------------------	-------------------------------	------------------------------

Signs and Symptoms of Exposure *INGESTION: Nausea, headache, vomiting. EYES: Moderate to severe irritation. INHALATION: Nausea, headache, dizziness, coordination impairment on long exposure. SKIN: Irritation due to defatting of tissue.*

Medical Conditions Generally Aggravated by Exposure *Skin allergies, chronic chemical sensitivity, asthma, emphysema.*

Emergency and First Aid Procedures *INGESTION: Do not induce vomiting, call physician. EYES: Flush with large amounts of water for 15 min. call physician. INHALATION: Remove to fresh air, give oxygen if breathing is difficult. SKIN: Wash with soap and water, remove contaminated clothing.*

Section VII -- Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

Shut off ignition sources, no flares, smoking or flames.

Use water to reduce vapors. Absorb spill with non-combustible absorbant material.

Waste Disposal Method

Wrap "empty" can in paper and place in trash.

For spill disposal, consult local authorities.

Precautions to Be Taken in Handling and Storing

Do not store where temperatures exceed 120°F.

Other Precautions

Avoid contact with skin or breathing of vapors. Wash with soap and water after handling. Keep out of reach of children.

Section VIII -- Control Measures

Respiratory Protection (*Specificity Type*)

If TLV is exceeded NIOSH/MSHA approved air supplied respirator.

Ventilation YES	Local Exhaust <i>Best</i>	Special <i>Not required</i>
	Mechanical (General) <i>OK</i>	Other <i>None required</i>

Protective Gloves <i>Chemical resistant</i>	Eye Protection <i>Goggles, chemical splash type.</i>
--	---

Other Protective Clothing or Equipment
Chemical resistant apron and gloves.

Work/Hygienic Practices

Good ventilation